


Verzonken kop met vleugeltjes

montage in staal - freesribben onder de kop



gecementeerd staal verzinkt

WINGTEKS / ZN

| BC | Ø | x | L | min K | max K | Ø kop | aandrijving | VE | code |
|--------|-----|---|-----|-------|-------|-------|-------------|-----|--------|
| 2 - 3 | 4,2 | x | 25 | - | 10 | 8,1 | PH 2 | 500 | 288200 |
| 2 - 3 | 4,2 | x | 35 | - | 20 | 8,1 | PH 2 | 500 | 288205 |
| 2 - 3 | 4,2 | x | 45 | - | 30 | 8,1 | PH 2 | 500 | 288210 |
| 3 - 4 | 4,8 | x | 25 | - | 8 | 9,1 | PH 2 | 500 | 288250 |
| 3 - 4 | 4,8 | x | 35 | - | 18 | 9,1 | PH 2 | 500 | 288350 |
| 3 - 4 | 4,8 | x | 45 | - | 28 | 9,1 | PH 2 | 500 | 288400 |
| 4 - 5 | 5,5 | x | 38 | - | 18 | 11 | PZ 3 | 100 | 288800 |
| 4 - 5 | 5,5 | x | 45 | - | 25 | 11 | PZ 3 | 100 | 288820 |
| 4 - 5 | 5,5 | x | 50 | - | 30 | 11 | PZ 3 | 100 | 288830 |
| 2 - 6 | 6,3 | x | 35 | - | 14 | 12,4 | PZ 3 | 100 | 288535 |
| 2 - 6 | 6,3 | x | 55 | - | 34 | 12,4 | PZ 3 | 100 | 288550 |
| 2 - 6 | 6,3 | x | 60 | - | 39 | 12,4 | PZ 3 | 100 | 288600 |
| 2 - 6 | 6,3 | x | 70 | - | 49 | 12,4 | PZ 3 | 100 | 288700 |
| 2 - 6 | 6,3 | x | 80 | 20 | 59 | 12,4 | PZ 3 | 100 | 288710 |
| 2 - 6 | 6,3 | x | 90 | 30 | 69 | 12,4 | PZ 3 | 100 | 288720 |
| 2 - 6 | 6,3 | x | 110 | 50 | 89 | 12,4 | PZ 3 | 100 | 288730 |
| 4 - 10 | 5,5 | x | 50 | - | 24 | 11 | PH 3 | 100 | 288831 |
| 4 - 10 | 5,5 | x | 80 | - | 54 | 11 | PH 3 | 100 | 288840 |
| 4 - 10 | 5,5 | x | 110 | 46 | 84 | 11 | PH 3 | 100 | 288850 |
| 4 - 10 | 5,5 | x | 130 | 66 | 104 | 11 | PH 3 | 100 | 288860 |

BC: boorcapaciteit door staal (minimum / maximum)

- ▶ behandeld staal supracoat 2C of 3C op aanvraag
- ▶ om hout op staal te verbinden