


### Metalen plug met hoog veiligheidsprestatievermogen - voorgemonteerd met schroef zeskantkop + ring

dubbele uitzetting

“verankeringsbout” - met Europese Technische Goedkeuring



gewicht tot 6.428 kg 

staal klasse 8.8 verzinkt  $\geq 5 \mu\text{m}$



**ATS-S EVO**

d	/	t <sub>fix</sub>	x	l	d <sub>0</sub>	h <sub>1</sub>	SW	VE	code
M 6	/	10	x	70	10	75	10	50	344418
M 6	/	20	x	80	10	75	10	50	344420
M 6	/	50	x	110	10	75	10	50	344422
M 8	/	10	x	80	12	85	13	25	344423
M 8	/	20	x	90	12	85	13	25	344424
M 8	/	50	x	120	12	85	13	25	344426
M 10	/	10	x	90	15	95	17	20	344425
M 10	/	20	x	100	15	95	17	20	344428
M 10	/	50	x	130	15	95	17	20	344430
M 10	/	100	x	180	15	95	17	20	344431
M 12	/	10	x	110	18	115	19	20	344419
M 12	/	25	x	125	18	115	19	20	344432
M 12	/	50	x	150	18	115	19	20	344434
M 12	/	100	x	200	18	115	19	20	344433
M 16	/	10	x	125	24	130	24	10	344435
M 16	/	25	x	140	24	130	24	10	344436
M 16	/	50	x	165	24	130	24	10	344438
M 16	/	100	x	215	24	130	24	10	344439

- ▶ bestemd voor: gescheurd en niet-gescheurd beton - toepassing voor zware belasting
- ▶ Europese Technische Goedkeuring ETA 10 / 0423 (M6 - M16) Optie 1 - Methode A
- ▶ veiligheidsplug type “verankeringsbout”
- ▶ hoge trek- en afschuif belastingscapaciteit
- ▶ voorgemonteerd